

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version STANDARD
 Type TL
 Tire Size 420/65 R 30
 LI/SS 136 D/139 A8

Dimensions (U/M International standard)

Section Width (mm) 418
 Overall Diameter (mm) 1308
 Static Loaded Radius (mm) 606
 Rolling Circumference (mm) 3952
 SRI 625
 Rim Rec W 13
 Rim Alt W 12 ; W 11



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1055	1210	1390	1570	1750	1930	2085	2240
50	1110	1275	1465	1650	1840	2030	2195	2355
40	1145	1315	1510	1705	1900	2090	2260	2430
25	1250	1435	1650	1860	2075	2285	2470	2655
10	1580	1815	2085	2355	2625	2890	3125	3360