

TECHNICAL SPECIFICATION

Applications Trailer / Implement Machinery / Hay Harvester / Baler

Description AW 711 is an implement radial tire specially designed for modern farming, and suitable for general purpose applications. Thanks to its special tread compound, the AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption.

Pattern Name **AW 711**

Version STUBBLE RESISTANT

US Code 94053292

Type TL

Tire Size 265/70 R 16.5

LI/SS 134 A8/B



Dimensions (U/M US Standard)

Section Width (in) 10.4

Overall Diameter (in) 30.4

Static Loaded Radius (in) 13.5

Rolling Circumference (in) 90

SRI 370

Rim Rec 8.25

ECE E11-106R-002978

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
30	1500	1970	2390	2770	3190	3600	3880	4250	4670
25	1500	1970	2390	2770	3190	3600	3880	4250	4670
20	1680	2200	2680	3100	3560	4030	4350	4770	5240
15	1790	2350	2840	3280	3790	4290	4630	5070	5570
10	1900	2480	3010	3480	4010	4540	4910	5370	5900
5	2110	2760	3340	3870	4450	5050	5450	5960	6550