

## TECHNICAL SPECIFICATION

**Applications** High Power Tractor

**Description** As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

**Pattern Name**      **AGRIMAX V - FLECTO**

**Version** STANDARD  
**US Code** 94053377  
**Type** TL  
**Tire Size** VF 710/60 R 42 NRO  
**LI/SS** 173 D



**Dimensions (U/M US Standard)**

**Section Width (in)** 28.0  
**Overall Diameter (in)** 76.0  
**Static Loaded Radius (in)** 33.9  
**Rolling Circumference (in)** 225.4  
**SRI** 925  
**Rim Rec** DW 25 B  
**Rim Alt** DW 23 B ; MW 25 B

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
45	7180	8350	9530	10700	11870	13040
5 TO 40	7880	9170	10460	11750	13040	14330
DUAL FITMENT	6950	8070	9210	10340	11480	12610