

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader
 Description: FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name **FL 630 SUPER**

Version: STANDARD
 US Code: 94053445
 Type: TL
 Tire Size: 710/50 R 26.5
 LI/SS: 170 D



Dimensions (U/M US Standard)
 Section Width (in): 28.6
 Overall Diameter (in): 54.4
 Static Loaded Radius (in): 24.6
 Rolling Circumference (in): 166.8
 SRI: 650
 Rim Rec: AG 24.00
 Rim Alt: AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3850	4450	5050	6130	7100	8180	9260	9980	11060	12010
40	4230	4890	5560	6750	7800	8990	10180	10980	12170	13230
30	5130	5930	6720	8170	9450	10890	12330	13290	14730	16000
25	5760	6670	7560	9180	10610	12230	13860	14940	16560	17990
15	6690	7740	8780	10660	12330	14220	16090	17350	19230	20900
5	7632	8820	10010	12150	14050	16190	18340	19760	21910	23810