

TECHNICAL SPECIFICATION

Applications: Telehandler
 Description: MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers in industrial applications. The tire shows an aggressive tread design providing excellent traction under any service condition. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

Pattern Name **MULTIMAX MP 527**

Version: STANDARD
 US Code: 94053483
 Type: TL
 Tire Size: 400/70 R 24 IND
 LI/SS: 152 A8/B



Dimensions (U/M US Standard)

Section Width (in): 15.9
 Overall Diameter (in): 46.1
 Static Loaded Radius (in): 21.3
 Rolling Circumference (in): 141.6
 SRI: 575
 Rim Rec: 13
 Rim Alt: DW 12 ; DW 13 ; DW 13 L ; 13 SDC ; DW 14 L
 ECE: E11-106R-003958

LOAD CAPACITY TABLE (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	3760	4460	5090	5800	6500	6970	7830	-	-
25	3760	4460	5090	5800	6500	6970	7830	-	-
20	4020	4780	5450	6210	6960	7460	8380	-	-
15	4180	4960	5650	6440	7220	7750	8700	-	-
5 Cyc.	4590	5640	6640	7640	8700	9460	10690	11280	11740
Static	7020	8640	10170	11710	13330	14490	16390	17280	18000