

TECHNICAL SPECIFICATION

Applications Trailer / Implement Machinery / Hay Harvester / Baler

Description AW 711 is an implement radial tire specially designed for modern farming, and suitable for general purpose applications. Thanks to its special tread compound, the AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption.

Pattern Name **AW 711**

Version STUBBLE RESISTANT

US Code 94053506

Type TL

Tire Size 305/70R16.5

LI/SS 148 A8/B



Dimensions (U/M US Standard)

Section Width (in) 12.8

Overall Diameter (in) 33.5

Static Loaded Radius (in) 14.6

Rolling Circumference (in) 100.5

SRI 410

Rim Rec 9.75

ECE E11-106R-002995

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
30	2080	2710	3340	3820	4450	5070	5420	5970	6540	6940
25	2080	2710	3340	3820	4450	5070	5420	5970	6540	6940
20	2340	3040	3740	4290	4980	5690	6070	6700	7320	7780
15	2480	3230	3970	4550	5290	6040	6450	7110	7770	8270
10	2630	3420	4210	4820	5610	6390	6830	7530	8230	8750
5	2920	3790	4670	5360	6230	7100	7580	8370	9150	9720