

## TECHNICAL SPECIFICATION

**Applications**                      Articulated Dump Truck (ADT)

**Description**                      Earthmax SR 35 is a low-profile All Steel radial tire specially designed for articulated dump trucks. It is ideal for operations requiring exceptional traction and flotation. Earthmax SR 35 provides both excellent traction and stability. Thanks to its strong steel-belted casing, it ensures extraordinary durability and resistance to snags and punctures. The tire is available as cut-resistant compound for a maximum service life even under severe conditions.

**Pattern Name**                    **EARTHMAX SR 35**

**Version**                              CUT RESISTANT COMPOUND

**US Code**                            94053636

**Type**                                 TL

**Tire Size**                          750/65 R 25

**LI/SS**                                190 B / 202 A2

**TMPH**                                151



**Dimensions (U/M US Standard)**

**Overall Diameter (in)**        63.0

**Static Loaded Radius (in)**    28.1

**Rolling Circumference (in)**   189.1

**Rim Rec**                          24.00/3.0

**Rim Alt**                            22.00/3.0 ; 25.00/3.0

**Star Rating**                      \*\*/\*\*

**LOAD CAPACITY TABLE (lbs)**

mph / psi	58	62	65	69
5	29100	30900	32000	33100
30	20900	21500	22700	23400