

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor

Description AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version SPECIAL
 US Code 94053711
 Type TL
 Tire Size 440/65 R 24
 LI/SS 135 D/138 A8

Dimensions (U/M US Standard)

Section Width (in) 17.4
 Overall Diameter (in) 46.5
 Static Loaded Radius (in) 21.2
 Rolling Circumference (in) 139.6
 SRI 575
 Rim Rec W 14 L
 Rim Alt W 13 ; W 15 L
 ECE E4-106R-000616



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	2310	2700	3030	3370	3700	3990	4430	4810
30	2420	2830	3190	3540	3890	4200	4650	5050
25	2500	2920	3280	3650	4010	4320	4790	5200
20	2660	3110	3490	3880	4270	4600	5090	5530
5 LT	3100	3620	4070	4520	4970	5360	5940	6450
5 HT	2660	3110	3490	3880	4270	4600	5090	5530