

## TECHNICAL SPECIFICATION

**Applications** Forklift

**Description** SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

**Pattern Name** **SUPER TRAX HD**

**Version** STANDARD  
**US Code** 94053759  
**Type** TT  
**Tire Size** 7.00 - 12  
**PR** 14



**Dimensions (U/M US Standard)**  
**Section Width (in)** 7.9  
**Overall Diameter (in)** 27.2  
**Static Loaded Radius (in)** 12.7  
**Rolling Circumference (in)** 82.2  
**Rim Rec** 5.00 S

**LOAD CAPACITY TABLE (lbs)**

mph / psi	131
15 LOAD WHEEL	6075
15 STEER WHEEL	4675
5 OTHER VEHICLES	6075
15 OTHER VEHICLES	4675
STATIC SIDE LOADER	7055

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%