

## TECHNICAL SPECIFICATION

**Applications** Tractor

**Description** AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

**Pattern Name**      **AGRIMAX ELOS**

Version                    STANDARD  
 US Code                 94053766  
 Type                      TL  
 Tire Size                480/80 R 38  
 LI/SS                    149 A8/B



Dimensions (U/M US Standard)

Section Width (in)      19.3  
 Overall Diameter (in)   71.0  
 Static Loaded Radius (in) 32.3  
 Rolling Circumference (in) 210.9  
 SRI                         875  
 Rim Rec                 W 16 L  
 Rim Alt                 W 15 L ; DW 16 L  
 ECE                      E11-106R-002991  
 TRA Code                R-2

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
30	3950	4590	5240	5870	6530	7160
25	3950	4590	5240	5870	6530	7160
20	4220	4920	5610	6290	6990	7670
5 LT	5290	6150	7010	7880	8740	9600
5 HT	4220	4920	5610	6290	6990	7670