

TECHNICAL SPECIFICATION

Applications Trailer
Description BK 826 has been specially designed for trailers in transport applications. It is a bias tire featuring excellent traction even under heavy-duty service conditions. BK 826 is also available as "industrial" version that shows particular cut-and-chip resistance and is also suitable for backhoe loaders.

Pattern Name **BK 826**
Version SPECIAL
US Code 94054879
Type TT
Tire Size 9.00 - 16
PR 12

Dimensions (U/M US Standard)
Section Width (in) 10.0
Overall Diameter (in) 36.4
Rim Rec 6.50 H
Rim Alt 6.00 G



LOAD CAPACITY TABLE (lbs)

mph / psi	75
20	4190

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..