

## TECHNICAL SPECIFICATION

Applications Tractor  
 Description RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. This winter tire for tractors ensures perfect grip for all operations on icy and snowy land without the need of snow chains being mounted. Thanks to the tread grooves and the special mix, a tractor can be driven in full stability, comfort and with maximum control at low temperatures even on roads that are both difficult and dangerous due to snow and ice.

**Pattern Name RIDEMAX IT 697 (M+S)**

Version STANDARD  
 US Code 94055418  
 Type TL  
 Tire Size 650/65 R 38  
 LI/SS 170 D/175 A8  
 TMPH 1



Dimensions (U/M US Standard)  
 Section Width (in) 25.4  
 Overall Diameter (in) 71.3  
 Static Loaded Radius (in) 32.4  
 Rolling Circumference (in) 217.1  
 SRI 875  
 Rim Rec DW 20 B  
 Rim Alt DW 18 L

**LOAD CAPACITY TABLE (lbs)**

mph / psi	17	23	29	35	41	46
40	6220	7670	8990	10450	11770	13230
30	6710	8290	9710	11290	12710	14290
25	7150	8820	10340	12010	13540	15210
20	7460	9200	10790	12540	14130	15870