

**TECHNICAL SPECIFICATION**

Applications                   Trailer / Implement Machinery / 2WD Tractor  
 Description                   INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features outstanding cut and chip resistance making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

**Pattern Name           INDUSTRIAL RIB F3**

Version                        STUBBLE RESISTANT  
 US Code                      94055500  
 Type                            TL  
 Tire Size                     11L - 15 SL  
 PR                              12



Dimensions (U/M US Standard)  
 Section Width (in)        11.0  
 Overall Diameter (in)     32.0  
 Rim Rec                     8 LB  
 Rim Alt                      10 LB

**LOAD CAPACITY TABLE (lbs)**

mph / psi	62
20	2840
25	2560

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.  
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..