

TECHNICAL SPECIFICATION

Applications Rototiller / Compact Utility Tractor
 Description TR 128 has been specially designed for utility tractors and rototillers. The wide and deep lug design provides an extended tire service life. TR128 features maximum traction on wet soil as well as superior self-cleaning properties and a strong nylon casing.

Pattern Name TR 128

Version STANDARD
 US Code 94055883
 Type TT
 Tire Size 5 - 12
 LI/SS 60 A8
 PR 6



Dimensions (U/M US Standard)
 Section Width (in) 5.0
 Overall Diameter (in) 21.8
 Static Loaded Radius (in) 10.4
 Rolling Circumference (in) 64.5
 Rim Rec 4 JA

LOAD CAPACITY TABLE (lbs)

mph / psi	52
25	550

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..