

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader

Description: RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption.

Pattern Name **RIDEMAX FL 693 M**

Version: STANDARD
 US Code: 94056132
 Type: TL
 Tire Size: 710/35 R 22.5
 LI/SS: 157 D/154 E



Dimensions (U/M US Standard)

Section Width (in): 28.0
 Overall Diameter (in): 42.1
 Static Loaded Radius (in): 19.0
 Rolling Circumference (in): 128.1
 SRI: 525
 Rim Rec: AG 24.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3020	3390	4220	4790	5540	6280	6870	7530	8270
40	3330	3740	4640	5280	6100	6910	7550	8280	9090
30	4020	4520	5620	6390	7390	8380	9150	10030	11010
25	4520	5080	6320	7180	8290	9400	10270	11260	12370
20	5020	5630	7010	7970	9200	10440	11410	12500	13730
15	5250	5900	7340	8340	9630	10930	11940	13080	14370
5	5990	6710	8360	9500	10970	12440	13590	14900	16370