

TECHNICAL SPECIFICATION

Applications: Trailer / Tanker / Spreader
 Description: FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name **FL 630 SUPER**

Version: STANDARD
 US Code: 94056149
 Type: TL
 Tire Size: 600/55 R 22.5
 LI/SS: 162 D



Dimensions (U/M US Standard)
 Section Width (in): 23.4
 Overall Diameter (in): 48.5
 Static Loaded Radius (in): 22.0
 Rolling Circumference (in): 147.9
 SRI: 575
 Rim Rec: AG 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3480	3910	4870	5530	6390	7250	7910	8690	9530
40	3820	4300	5350	6070	7020	7960	8700	9530	10470
30	4630	5200	6470	7350	8500	9630	10530	11540	12680
25	5200	5840	7260	8270	9550	10820	11830	12960	14240
15	6040	6790	8440	9600	11090	12580	13730	15060	16540
5	6890	7740	9620	10930	12630	14330	15650	17160	18850