

TECHNICAL SPECIFICATION

Applications Forklift

Description SUPER TRAX HD has been specifically engineered for forklifts in heavy-duty material handling operations, including port and mining applications. The extra deep tread is made of a unique wear-resistant tread compound ensuring a longer service life. SUPER TRAX HD features a strong casing and a reinforced sidewall resulting in both excellent stability and maneuvering in lift mode. The specially designed rim guard provides protection against flats and wheel damage in the rim flange area.

Pattern Name **SUPER TRAX HD**

Version STANDARD
US Code 94056552
Type TT
Tire Size 8.15 - 15
PR 14

Dimensions (U/M US Standard)

Section Width (in) 8.7
Overall Diameter (in) 28.1
Static Loaded Radius (in) 13.1
Rolling Circumference (in) 85.4
Rim Rec 7.00
Rim Alt 7 BD



LOAD CAPACITY TABLE (lbs)

mph / psi	145
15 LOAD WHEEL	8600
15 STEER WHEEL	6615
5 OTHER VEHICLES	8600
15 OTHER VEHICLES	6615
STATIC SIDE LOADER	9985

* Tolerances: Overall Diameter $\pm 2\%$ | Section Width $\pm 2\%$ | Rolling Circumference $\pm 2.5\%$