

## TECHNICAL SPECIFICATION

Applications                    ATV  
 Description                    AT 171 is suitable for on-and-off-the-road applications with ATV vehicles. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces. AT 171 comes up with optimum self-cleaning properties along with extraordinary cut and chip resistance. The strong casing ensures extra durability and a long service life.

**Pattern Name            AT 171**  
 Version                    STANDARD  
 US Code                    94056842  
 Type                        TL  
 Tire Size                   AT 31 X 9 - 16  
 LI/SS                      80 A8 / 56 F  
 PR                         6  
 TMPH                      1



Dimensions (U/M US Standard)  
 Section Width (in)        8.3  
 Overall Diameter (in)    30.9  
 Rim Rec                    W 7  
 Rim Alt                     W 6

**LOAD CAPACITY TABLE (lbs)**

mph / psi	20	15
25 MUD BOGGING	992	-
50 MUD BOGGING	494	-
25 CASUAL TRANSPORT	-	815
50 CASUL TRANSPORT	-	420

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..