

## TECHNICAL SPECIFICATION

**Applications**                    ATV

**Description**                    AT 171 is suitable for on-and-off-the-road applications with ATV vehicles. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces. AT 171 comes up with optimum self-cleaning properties along with extraordinary cut and chip resistance. The strong casing ensures extra durability and a long service life.

**Pattern Name**                **AT 171**

Version                            STANDARD

US Code                          94056880

Type                                TL

Tire Size                         AT 33 X 9 - 20

LI/SS                             85 A8 / 61 F

PR                                 6

TMPH                             1



**Dimensions (U/M US Standard)**

Section Width (in)            8.1

Overall Diameter (in)        33.0

Static Loaded Radius (in)   15.2

Rolling Circumference (in)   103

Rim Rec                         W 7

Rim Alt                         W 6

**LOAD CAPACITY TABLE (lbs)**

mph / psi	20	15
25 MUD BOGGING	1136	-
50 MUD BOGGING	567	-
25 CASUAL TRANSPORT	-	995
50 CASUL TRANSPORT	-	480

\* Tolerances: Overall Diameter  $\pm$  2% | Section Width  $\pm$  2% | Rolling Circumference  $\pm$  2.5%