

**TECHNICAL SPECIFICATION**

Applications                      Trailer / Implement Machinery  
 Description                      RIB 774 (A) is a low section implement tire offering high load capacity with minimum soil compaction. It is ideal for modern farming and suitable for on- and off-the-road applications.

**Pattern Name                      RIB 774 (A)**

Version                              STANDARD  
 US Code                            94056910  
 Type                                 TL  
 Tire Size                          18 X 8.50 - 8



Dimensions (U/M US Standard)  
 Section Width (in)              10.0  
 Overall Diameter (in)          18.1  
 Static Loaded Radius (in)      8.5  
 Rolling Circumference (in)    54.7  
 Rim Rec                            7.00 I - 55 ; I - 70 ; I - 90  
 ECE                                 E11-106R-004622

**LOAD CAPACITY TABLE (lbs)**

mph / psi	44
5 FR	1590
15 FR	1360
20 FR	1270
25 FR	1140

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..