

TECHNICAL SPECIFICATION

Applications Skid Steer
Description SKID POWER PLUS has been designed for skid steers in construction applications. Its wider lugs provide excellent traction as well as enhanced self-cleaning properties. The tire features an extra deep tread along with enhanced sidewall protection providing excellent cut-and-chip resistance and outstanding durability. SKID POWER PLUS is the ideal tire for loose surfaces. The wide contact area provides excellent stability during operations.

Pattern Name SKID POWER PLUS

Version SPECIAL
US Code 94057412
Type TL
Tire Size 10 - 16.5
PR 10



Dimensions (U/M US Standard)
Section Width (in) 9.9
Overall Diameter (in) 30.5
Rim Rec 8.25

LOAD CAPACITY TABLE (lbs)

mph / psi	75
5	4710
10	3710
15	3440

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..