

TECHNICAL SPECIFICATION

Applications Tractor
 Description TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Also in the harshest operating conditions, TR 171 provides excellent traction and extraordinary durability.

Pattern Name TR 171

Version HD
 US Code 94057610
 Type TT
 Tire Size 9.5 - 20
 LI/SS 104 A8
 PR 8
 TMPH 1



Dimensions (U/M US Standard)
 Section Width (in) 9.3
 Overall Diameter (in) 37.4
 Static Loaded Radius (in) 17.7
 Rolling Circumference (in) 115.8
 Rim Rec W 8
 Rim Alt W 7

LOAD CAPACITY TABLE (lbs)

mph / psi	42
25	1980

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..