

TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name AGRIMAX RT 855

Version: STANDARD
 US Code: 94057993
 Type: TL
 Tire Size: 520/85 R 50
 LI/SS: 165 A8/B
 TMPH: 1



Dimensions (U/M US Standard)
 Section Width (in): 20.3
 Overall Diameter (in): 84.8
 Static Loaded Radius (in): 39.1
 Rolling Circumference (in): 254.8
 SRI: 1025
 Rim Rec: DW 16L
 Rim Alt: DW 18 L

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	5350	6140	7045	7950	8865	9770	10685	11355
25	5350	6140	7045	7950	8865	9770	10685	11355
20	5725	6570	7540	8525	9495	10465	11435	12160
5 LT	7165	8225	9450	10660	11885	13095	14320	15225
5 HT	5725	6570	7540	8525	9495	10465	11435	12160