

## TECHNICAL SPECIFICATION

**Applications** High Power Tractor

**Description** As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

**Pattern Name**      **AGRIMAX V - FLECTO**

**Version** STANDARD  
**US Code** 94058495  
**Type** TL  
**Tire Size** VF 600/60 R 28 NRO  
**LI/SS** 157 D  
**TMPH** 1



**Dimensions (U/M US Standard)**

**Section Width (in)** 23.1  
**Overall Diameter (in)** 56.7  
**Static Loaded Radius (in)** 24.9  
**Rolling Circumference (in)** 166.5  
**SRI** 675  
**Rim Rec** DW 20 B  
**Rim Alt** DW 18 L

**LOAD CAPACITY TABLE (lbs)**

mph / psi	9	12	15	17	20	23
50	4010	4660	5310	5970	6620	8270
From 5 to 40 mph	4410	5130	5840	6570	7290	9095
DUAL FITMENT	3880	4520	5150	5790	6420	8000