

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD
 US Code 94058532
 Type TL
 Tire Size 420/85 R 34
 LI/SS 147 A8/B

Dimensions (U/M US Standard)

Section Width (in) 17.2
 Overall Diameter (in) 62.1
 Static Loaded Radius (in) 27.9
 Rolling Circumference (in) 184.1
 SRI 750
 Rim Rec W 15 L
 Rim Alt W 13 ; W 14 L



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	3200	3670	4210	4750	5290	5830	6380	6780
25	3200	3670	4210	4750	5290	5830	6380	6780
20	3420	3920	4510	5090	5680	6250	6830	7260
5 LT	4280	4920	5640	6370	7100	7830	8550	9090
5 HT	3420	3920	4510	5090	5680	6250	6830	7260