

TECHNICAL SPECIFICATION

Applications Tractor

Description AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version STANDARD
 US Code 94058617
 Type TL
 Tire Size 710/70 R 38
 LI/SS 178 A8/B
 TMPH 1



Dimensions (U/M US Standard)

Section Width (in) 28.2
 Overall Diameter (in) 79.5
 Static Loaded Radius (in) 36.0
 Rolling Circumference (in) 240.3
 SRI 975
 Rim Rec DW 23 B
 Rim Alt DW 25 B
 ECE E11-106R-004896

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
30	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
25	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
20	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690
5 LT	8200	9530	10860	12410	13750	15070	16620	17500	19280	20830	22160
5 HT	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690