

TECHNICAL SPECIFICATION

Applications Spreader / Harvester
 Description Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

Pattern Name AGRIMAX TERIS

Version STANDARD
 US Code 94058723
 Type TL
 Tire Size IF 710/75 R 34 CFO
 LI/SS 184 A8/B
 TMPH 1



Dimensions (U/M US Standard)
 Section Width (in) 28.2
 Overall Diameter (in) 76.0
 Static Loaded Radius (in) 34.3
 Rolling Circumference (in) 230.4
 Rim Rec DW 25 B

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840
25	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840
20	8290	9560	10840	12320	13590	15080	16780	18050	19750	21230
10 Cyc	12780	14740	16700	18990	20950	23250	25870	27830	30460	32740
5 Cyc	13930	16070	18220	20720	22860	25360	28220	30360	33220	35710