

TECHNICAL SPECIFICATION

Applications High Power Tractor
 Description AGRIMAX FORTIS is your reliable partner for all preparation, planting and soil treatment operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads maximizing your business productivity.

Pattern Name AGRIMAX FORTIS

Version SPECIAL
 US Code 94058907
 Type TL
 Tire Size 650/85 R 38
 LI/SS 173 D/176 A8



Dimensions (U/M US Standard)

Section Width (in) 26.6
 Overall Diameter (in) 81.5
 Static Loaded Radius (in) 36.8
 Rolling Circumference (in) 243.5
 SRI 975
 Rim Rec DW 23 B
 Rim Alt DW 21 B ; DW 20 B

LOAD CAPACITY TABLE (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 6880 | 8020 | 9030 | 10030 | 11030 | 11890 | 13180 | 14300 |
| 30 | 7230 | 8430 | 9480 | 10540 | 11600 | 12490 | 13840 | 15050 |
| 25 | 7520 | 8770 | 9870 | 10960 | 12060 | 13000 | 14410 | 15650 |
| 20 | 7910 | 9240 | 10380 | 11540 | 12700 | 13680 | 15170 | 16480 |
| 5 LT | 9230 | 10760 | 12100 | 13450 | 14790 | 15940 | 17670 | 19200 |
| 5 HT | 7910 | 9240 | 10380 | 11540 | 12700 | 13680 | 15170 | 16480 |