

TECHNICAL SPECIFICATION

Applications: Spreader / Harvester
 Description: Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations.

Pattern Name AGRIMAX TERIS

Version: STANDARD
 US Code: 94059249
 Type: TL
 Tire Size: IF 710/75 R 32 CFO
 LI/SS: 183 A8/B



Dimensions (U/M US Standard)
 Section Width (in): 28.2
 Overall Diameter (in): 74.0
 Static Loaded Radius (in): 33.5
 Rolling Circumference (in): 222.6
 SRI: 925
 Rim Rec: DW 25 B
 Rim Alt: DW 23 B

LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	20	23	29	35	41	46
30	7530	8870	10230	12730	13890	15240	16400	17940	19300
25	7530	8870	10230	12730	13890	15240	16400	17940	19300
20	8060	9500	10950	13630	14870	16310	17560	19200	20650
10 Cyc.	11670	13760	15850	19740	21540	23630	25430	27820	29900
5 Cyc.	13550	15970	18410	22920	25000	27440	29520	32300	34720