

TECHNICAL SPECIFICATION

Applications Trailer / Tanker / Spreader
 Description FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

Pattern Name FL 630 SUPER

Version STANDARD
 US Code 94059539
 Type TL
 Tire Size 560/60 R 22.5
 LI/SS 165 D



Dimensions (U/M US Standard)
 Section Width (in) 21.4
 Overall Diameter (in) 49.0
 Static Loaded Radius (in) 21.6
 Rolling Circumference (in) 149
 SRI 600
 Rim Rec AG 16.00
 Rim Alt 17.00 ; 20.00

LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3780	4240	5280	6010	6930	7860	8590	9410	10340
40	4140	4660	5800	6590	7620	8630	9420	10340	11350
30	5030	5640	7010	7980	9210	10450	11420	12510	13750
25	5640	6340	7880	8960	10350	11740	12820	14050	15440
15	6560	7360	9160	10420	12030	13650	14900	16340	17940
5	7460	8390	10430	11860	13700	15540	16960	18610	20440