

TECHNICAL SPECIFICATION

Applications Implement Machinery
 Description AW 712 is an implement radial tire that is particularly suitable for slurry tank trucks and trailers. It features a strong casing in addition to a stubble-resistant compound to ensure great durability. AW 712 provides also excellent driving comfort.

Pattern Name AW 712
 Version IMPLEMENT
 US Code 94059584
 Type TL
 Tire Size 260/70 R 15.3
 LI/SS 134 A8/B



Dimensions (U/M US Standard)
 Section Width (in) 10.4
 Overall Diameter (in) 29.9
 Static Loaded Radius (in) 13.5
 Rolling Circumference (in) 90.7
 Rim Rec 9.00

LOAD CAPACITY TABLE (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	58	73
30	1360	1730	2110	2440	2810	3190	3420	3790	3920	4400	4670
25	1360	1730	2110	2440	2810	3190	3420	3790	3920	4400	4670
20	1520	1940	2360	2720	3140	3560	3820	4240	4390	4930	5240
15	1620	2060	2510	2900	3340	3790	4070	4520	4660	5240	5570
10	1720	2180	2660	3080	3540	4010	4310	4780	4940	5540	5900
5	1910	2420	2950	3410	3940	4450	4780	5310	5490	6160	6550