

TECHNICAL SPECIFICATION

Applications Trailer / Implement Machinery / Compact Dumper
 Description FLOTATION TR 675 is best suited for soil tillage operations and transport. It fits trailers, compact dumpers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction remaining gentle on the ground to prevent crop damages.

Pattern Name FLOTATION TR 675

Version STEEL BELTED
 US Code 94059959
 Type TL
 Tire Size 540/60 - 28
 LI/SS 155 A8/161 A2
 PR 16



Dimensions (U/M US Standard)
 Section Width (in) 20.9
 Overall Diameter (in) 56.1
 Rim Rec W 16 L
 Rim Alt W 18 L

LOAD CAPACITY TABLE (lbs)

mph / psi	48
25	8550

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..