

TECHNICAL SPECIFICATION

Applications High Power Tractor

Description AGRIMAX FORCE, the high-end product of BKT, is a radial tire specially designed for agriculture applications with high-power tractors, ensuring top performance and efficiency. AGRIMAX FORCE is a really comfortable tire for both field operations and road transfers; it actually allows to move without the need for increasing the inflation pressure.

Pattern Name **AGRIMAX FORCE**

Version SPECIAL

US Code 94060054

Type TL

Tire Size IF 650/65 R 34 CFO

LI/SS 161 D



Dimensions (U/M US Standard)

Section Width (in) 25.6

Overall Diameter (in) 67.3

Static Loaded Radius (in) 30.1

Rolling Circumference (in) 199.9

SRI 825

Rim Rec DW 23 B

LOAD CAPACITY TABLE (lbs)

mph / psi*	9	12	15	17	20	23
45	5190	6120	6940	7790	8530	9270
From 40 to 25	5710	6720	7640	8560	9380	10200
20	5930	6990	7940	8910	9750	10600
12	6160	725	8240	9250	10130	11010
5	7240	8530	9700	10870	11900	12940
5 Cyc*	7990	9410	10690	11980	13130	14270
5HT	5930	6990	7940	8910	9750	10600

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.