

## TECHNICAL SPECIFICATION

Applications: Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler  
 Description: AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

**Pattern Name**      **AS 504**  
 Version: STANDARD  
 US Code: 94060092  
 Type: TL  
 Tire Size: 400/50 - 15



Dimensions (U/M US Standard)  
 Section Width (in): 15.6  
 Overall Diameter (in): 31.1  
 Static Loaded Radius (in): 14.5  
 Rolling Circumference (in): 94  
 Rim Rec: 13 LB  
 ECE: E11-106R-005494

**LOAD CAPACITY TABLE (lbs)**

mph / psi	44
5 FR	4480
15 FR	3800
20 FR	3580
25 FR	3200
5 DW	3170
15 DW	2700
20 DW	2550
25 DW	2270

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%