

TECHNICAL SPECIFICATION

Applications: Loader / Grader
 Description: EARTHMAX SR 23 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders. It features superior forward and lateral traction as well as exceptional self-cleaning properties. The durable casing and the particularly cut-resistant tread provide a long service life.

Pattern Name EARTHMAX SR 23

Version: STANDARD
 US Code: 94060313
 Type: TL
 Tire Size: 17.5 R 25
 LI/SS: 176 A2/153 A8



Dimensions (U/M US Standard)
 Overall Diameter (in): 53.0
 Static Loaded Radius (in): 24.1
 Rolling Circumference (in): 161.7
 Rim Rec: 14.00/1.5
 Rim Alt: 14.00/1.3 (DC)
 Star Rating: *

LOAD CAPACITY TABLE (lbs)

| mph / psi | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 5 | - | - | - | - | - | - | - | - | 13200 | 13600 | 14300 | 14800 | 15700 |
| 25 | 4080 | 4680 | 5200 | 5840 | 6400 | 6800 | 7400 | 8050 | - | - | - | - | - |