

## TECHNICAL SPECIFICATION

Applications                      Trailer / Tanker / Spreader  
 Description                      FL 630 SUPER is suitable for trailers, tankers and spreaders. Thanks to its constructive features and tread design, FL630 SUPER is the ideal tire for multipurpose use on any kind of land or on the road, where qualities like uniform drive and resistance are further highlighted.

**Pattern Name                      FL 630 SUPER**

Version                              STANDARD  
 US Code                            94060900  
 Type                                 TL  
 Tire Size                          600/50 R 22.5  
 LI/SS                                159 D

Dimensions (U/M US Standard)

Section Width (in)                24.1  
 Overall Diameter (in)            46.1  
 SRI                                  550  
 Rim Rec                            AG 20.00  
 ECE                                 E11-106R-005992



LOAD CAPACITY TABLE (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3210	3600	4490	5100	5890	6680	7300	8000	8780
40	3530	3960	4930	5600	6470	7330	8010	8780	9645
30	4270	4790	5960	6780	7830	8870	9690	10630	11670
25	4790	5380	6690	7620	8800	9980	10890	11940	13120
15	5570	6260	7780	8850	10220	11600	12650	13880	15240
5	6340	7120	8860	10070	11640	13190	14420	15810	17360