

TECHNICAL SPECIFICATION

Applications High Power Tractor

Description As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

Pattern Name **AGRIMAX V - FLECTO**

Version STANDARD
US Code 94062102
Type TL
Tire Size VF 650/65 R 42 NRO
LI/SS 174 D

Dimensions (U/M US Standard)

Section Width (in) 25.6
Overall Diameter (in) 75.3
Static Loaded Radius (in) 33.5
Rolling Circumference (in) 224.3
SRI 925
Rim Rec DW 23 B
Rim Alt DW 21 B
ECE E11-106R-005713
TRA Code R-1W



LOAD CAPACITY TABLE (lbs)

| mph / psi* | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|---------------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 6840 | 7910 | 8990 | 10210 | 11140 | 12090 | 13440 |
| from 40 to 25 | 7530 | 8710 | 9890 | 11220 | 12260 | 13290 | 14770 |
| 20 | 7670 | 8870 | 10070 | 11440 | 12500 | 13560 | 15060 |
| 12 | 7830 | 9050 | 10270 | 11660 | 12740 | 13820 | 15350 |
| 5 | 8280 | 9580 | 10870 | 12330 | 13480 | 14620 | 16250 |
| 5 Cyc* | 10540 | 12190 | 13830 | 15710 | 17150 | 18610 | 20680 |
| 5 HT | 7670 | 8870 | 10070 | 11440 | 12500 | 13560 | 15060 |

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.