

## TECHNICAL SPECIFICATION

**Applications** High Power Tractor

**Description** As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

**Pattern Name** **AGRIMAX V - FLECTO**

**Version** STANDARD  
**US Code** 94062126  
**Type** TL  
**Tire Size** VF 540/65 R 28 NRO  
**LI/SS** 154 D

**Dimensions (U/M US Standard)**

**Section Width (in)** 21.2  
**Overall Diameter (in)** 55.6  
**Static Loaded Radius (in)** 24.5  
**Rolling Circumference (in)** 162  
**SRI** 675  
**Rim Rec** DW 20 B  
**Rim Alt** DW 18 L  
**ECE** E11-106R-005710  
**TRA Code** R-1W



**LOAD CAPACITY TABLE (lbs)**

mph / psi*	9	12	15	17	20	23
45	4210	4960	5630	6320	6910	7520
from 40 to 25	4630	5460	6190	6940	7610	8270
20	4720	5560	6320	7080	7750	8430
12	4810	5670	6440	7220	7900	8600
5	5090	6000	6810	7640	8370	9090
5 Cyc*	6480	7640	8660	9720	10650	11570
5 HT	4720	5560	6320	7080	7750	8430

\* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.