

TECHNICAL SPECIFICATION

Applications High Power Tractor

Description As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

Pattern Name **AGRIMAX V - FLECTO**

Version STANDARD
US Code 94062133
Type TL
Tire Size VF 540/65 R 30 NRO
LI/SS 158 D



Dimensions (U/M US Standard)

Section Width (in) 21.2
Overall Diameter (in) 57.6
Static Loaded Radius (in) 25.6
Rolling Circumference (in) 170
SRI 700
Rim Rec DW 20 B
Rim Alt DW 18 L
ECE E11-106R-005711
TRA Code R-1W

LOAD CAPACITY TABLE (lbs)

mph / psi*	9	12	15	17	20	23	29
45	4340	5020	5700	6470	7070	7670	8520
from 40 to 25	4770	5520	6270	7120	7770	8430	9370
20	4860	5630	6390	7250	7930	8600	9560
12	4960	5740	6510	7400	8080	8760	9740
5	5250	6070	6890	7830	8540	9270	10310
5 Cyc*	6680	7730	8770	9960	10880	11810	13120
5 HT	4860	5630	6390	7250	7930	8600	9560

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.