

TECHNICAL SPECIFICATION

Applications Implement Machinery
 Description FLOTATION 647 is an implement tire that features best traction on soft soil and grassland. In addition to excellent self-cleaning properties, the specially designed tread pattern provides a wide contact area, which ensures optimized ground pressure and excellent performance on soft soil.

Pattern Name FLOTATION 647

Version STANDARD
 US Code 94062768
 Type TL
 Tire Size 260/75 - 15.3



Dimensions (U/M US Standard)
 Section Width (in) 10.8
 Overall Diameter (in) 30.9
 Static Loaded Radius (in) 14.3
 Rolling Circumference (in) 93.7
 Rim Rec 9.00
 ECE E11-106R-005838

LOAD CAPACITY TABLE (lbs)

mph / psi	80
25 FR	4300
25 DW	3000

* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..