

TECHNICAL SPECIFICATION

Applications Loader / Grader
 Description EARTHMAX SR 22 (G-2/L-2) is an All Steel radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

Pattern Name EARTHMAX SR 22

Version STANDARD
 US Code 94062911
 Type TL
 Tire Size 23.5 R 25
 LI/SS 195 A2/170 A8



Dimensions (U/M US Standard)
 Overall Width (in) 24.0
 Overall Diameter (in) 63.5
 Static Loaded Radius (in) 27.9
 Rolling Circumference (in) 191.5
 Rim Rec 19.50/2.5
 Star Rating *
 TRA Code G2/L2

LOAD CAPACITY TABLE (lbs)

| mph / psi | 18 | 22 | 25 | 29 | 33 | 36 | 40 | 44 | 58 | 62 | 65 | 69 | 73 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 5 | - | - | - | - | - | - | - | - | 22700 | 23400 | 24700 | 25400 | 26800 |
| 25 | 6950 | 7850 | 8800 | 9900 | 10700 | 11700 | 12300 | 13200 | - | - | - | - | - |