

## TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer  
 Description AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

**Pattern Name      AGRIMAX RT 765**

Version                STANDARD  
 US Code              94063109  
 Type                  TL  
 Tire Size              480/70 R 34  
 LI/SS                 155 D

Dimensions (U/M US Standard)

Section Width (in)    18.9  
 Overall Diameter (in) 62.2  
 Static Loaded Radius (in) 28.0  
 Rolling Circumference (in) 187.4  
 SRI                     750  
 Rim Rec                W 15 L  
 Rim Alt                 W 14 L ; W 16 L  
 ECE                     E11-106R-005834



LOAD CAPACITY TABLE (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	47
40	3260	3850	4430	4930	5510	6020	6600	7100	7770	8340
30	3430	4030	4650	5180	5790	6320	6930	7450	8160	8760
25	3570	4210	4850	5400	6040	6580	7220	7770	8500	9140
20	3750	4420	5090	5670	6340	6920	7590	8170	8940	9600
5 LT	4360	5150	5930	6600	7390	8060	8840	9510	10410	11190
5 HT	3750	4420	5090	6600	6340	6920	7590	8170	8940	9600