

AGRI GRIP - Spécifications techniques



Description

AGRI GRIP est un pneu pour les opérations de transport et il est particulièrement approprié pour les applications avec remorques pour canne à sucre. AGRI GRIP est équipé d'une carcasse robuste qui offre une capacité de charge élevée en même temps qu'une excellente résistance aux coupures et lacérations. Le dessin particulier de la bande de roulement assure un long cycle de vie.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	595
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4658
Rim Rec	DW 20 B

Load capacity (Kg)

km/h / bar	2.60
30 FR LLV	5600

Printed on 24/04/2024 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..