

## AGRIMAX ELOS - Spécifications techniques



### Description

AGRIMAX ELOS a été conçu pour assurer la plus grande traction même dans des conditions particulièrement difficiles sur terrains mouillés - tels les rizières - et marécageux. Le dessin de la bande de roulement a été élaboré spécialement pour garantir d'excellentes qualités d'auto-nettoyage, ce qui est fondamental lors des travaux dans les champs boueux et pendant les transferts. Pour optimiser la productivité de l'entreprise agricole, des bourrelets de protection sur les flancs ont été insérés dans le dessin du pneu AGRIMAX ELOS pour assurer à tout moment la plus grande protection contre d'éventuels dommages.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	710/70 R 38
LI/SS	178 A8/B

## Dimensions US Standard

Usa code	94058617
Section Width (inch)	28.2
Overall Diameter (inch)	79.5
Static Loaded Radius (inch)	36
Rolling Circumference (inch)	240.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-004896
TRA Code	R2

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
30	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
25	6120	7110	8100	9260	10250	11240	12400	13060	14380	15540	16530
20	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690
5 LT	8200	9530	10860	12410	13750	15070	16620	17500	19280	20830	22160
5 HT	6550	7620	8670	9910	10980	12040	13270	13980	15400	16630	17690

Printed on 18/04/2024 18:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..