

AGRIMAX FORCE - Spécifications techniques



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Tracteur de forte puissance

Version	STANDARD
Type	TL
Tyre Size	IF 650/85 R 42 CFO
LI/SS	180 D

Dimensions International Standard

Section Width (mm)	650
Overall Diameter (mm)	2173
Static Loaded Radius (mm)	965
Rolling Circumference (mm)	6400
SRI (mm)	1025
Rim Rec	DW 23 B
ECE	E4-106R-001832
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3420	3930	4510	5095	5675	6260	6840	7280
From 65 to 40	3760	4320	4960	5600	6240	6880	7520	8000
30	3910	4490	5155	5820	6485	7155	7820	8320
20	4060	4665	5355	6045	6735	7430	8120	8640
10	4775	5485	6295	7110	7920	8735	9550	10160
Upto 30 Cyc	4885	5615	6445	7280	8110	8940	9775	10400
Upto 15 Cyc	5825	6695	7685	8680	9670	10660	11655	12400
Upto 10 Cyc	6390	7340	8430	9520	10605	11695	12780	13600
10 HT	3910	4490	5155	5820	6485	7155	7820	8320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 01/05/2025 06:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..