

## AGRIMAX FORTIS - Spécifications techniques



### Description

AGRIMAX FORTIS est un partenaire fiable pour toutes vos opérations de préparation, plantation et traitement du terrain et les applications de transport. Conçu pour équiper les tracteurs plus puissants de la nouvelle génération, AGRIMAX FORTIS vous permet de transporter des charges très lourdes avec une vitesse jusqu'à 65 km/h. Le pneu se distingue par une manœuvrabilité et un confort excellent/s pour assurer une expérience extraordinaire de conduite. La carcasse renforcée en nylon garantit une productivité augmentée dans les champs en conservant le sol grâce au compactage réduit.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Pulvérisateur

Version	STANDARD
Type	TL
Tyre Size	800/70 R 38
LI/SS	178 D/181 A8

## Dimensions US Standard

Usa code	94032969
Section Width (inch)	31.4
Overall Diameter (inch)	82.1
Static Loaded Radius (inch)	35.9
Rolling Circumference (inch)	244.2
Rim Rec	DW 25 B
Rim Alt	DW 27 B
ECE	E4-106R-001424
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	7940	9260	10420	11570	12730	13720	15210	16500
30	8330	9720	10950	12160	13370	14420	15970	17360
25	8730	10180	11460	12730	14010	15100	16730	18190
20	9130	10650	11980	13320	14650	15780	17490	19010
5 LT	10640	12410	13970	15510	17060	18400	20390	22160
5 HT	9130	10650	11980	13320	14650	15780	17490	19010

Printed on 27/04/2024 08:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..