

AGRIMAX RI 818 - Spécifications techniques



Description

AGRIMAX RI 818 est un pneu radial développé pour les applications d'arrosage avec des arroseurs à pivot. Le dessin particulier de la bande de roulement garantit une excellente traction dans les conditions humides et mouillés avec des propriétés élevées d'auto-nettoyage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Arroseur à pivot

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 320/85 R 38 (12.4 R 38) |
| LI/SS | 154 |

Dimensions International Standard

| | |
|----------------------------|------------|
| Section Width (mm) | 319 |
| Overall Diameter (mm) | 1509 |
| Static Loaded Radius (mm) | 691 |
| Rolling Circumference (mm) | 4565 |
| SRI (mm) | 725 |
| Rim Rec | W 10 |
| Rim Alt | W 9 ; W 11 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 1.6 |
| CREEP | 3750 |

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN) / For CREEP loads inflation pressure to be increased by +6 psi

Printed on 23/04/2024 18:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..