

AGRIMAX RT 765M - Spécifications techniques



Description

AGRIMAX RT 765M, un pneu de la série 70 de BKT, est idéal pour équiper les tracteurs les plus modernes utilisés dans les applications lourdes, telles que traitements de terrains, déplacements aux champs et sur route, vendange et pulvérisations. La large zone de contact garantit une traction et un confort optimaux sur toutes les surfaces et à tout moment. Le pneu se distingue de par ses excellentes qualités d'autonettoyage et le compactage du sol réduit. Deux tailles sont disponibles avec la technologie de ceintures en acier.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Tracteur • Machine à vendanger

Version	SPECIAL
Type	TL
Tyre Size	710/70 R 38
LI/SS	166 D

Dimensions US Standard

Usa code	94066780
Section Width (inch)	28.2
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	33.8
Rolling Circumference (inch)	226.4
Rim Rec	DW 23 B
ECE	E11-106R-005837
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	6430	7480	8530	9590	10640	11680
30	6760	7860	8960	10060	11170	12270
25	7040	8200	9350	10500	11650	12800
20	7400	8610	9810	11020	12230	13440
5 LT	8620	10030	11440	12850	14260	15660
5 HT	7400	8610	9810	11020	12230	13440

Printed on 26/04/2024 11:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..