

## AGRIMAX RT 945 - Spécifications techniques



### Description

AGRIMAX RT 945 a été conçu tout particulièrement pour les cultures en couloir : il n'abîme pas les cultures et il protège les récoltes. Qui plus est, ses capacités exceptionnelles d'auto-nettoyage permettent de passer rapidement du travail aux champs à une utilisation sur route, sur laquelle AGRIMAX RT 945 fait preuve d'une efficacité surprenante. La carcasse robuste assure une grande stabilité, une traction excellente et une durabilité extraordinaire.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Pulvérisateur • Tracteur

Version	STANDARD
Type	TL
Tyre Size	320/90 R 46 (12.4 R 46)
LI/SS	148 D/151 A8

## Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1744
Static Loaded Radius (mm)	810
Rolling Circumference (mm)	5232
SRI (mm)	825
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-004068
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	1355	1765	2145	2365	2490	2745	2965	3150
50	1425	1855	2255	2485	2615	2880	3115	3310
40	1485	1935	2350	2590	2730	3005	3245	3450
30	1560	2030	2465	2715	2860	3150	3405	3620
10	2035	2650	3215	3545	3735	4115	4445	4725

Printed on 23/04/2024 18:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..