

AGRIMAX RT 945 - Spécifications techniques



Description

AGRIMAX RT 945 a été conçu tout particulièrement pour les cultures en couloir : il n'abîme pas les cultures et il protège les récoltes. Qui plus est, ses capacités exceptionnelles d'auto-nettoyage permettent de passer rapidement du travail aux champs à une utilisation sur route, sur laquelle AGRIMAX RT 945 fait preuve d'une efficacité surprenante. La carcasse robuste assure une grande stabilité, une traction excellente et une durabilité extraordinaire.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Pulvérisateur • Tracteur

Version	STANDARD
Type	TL
Tyre Size	380/90 R 46 (14.9 R 46)
LI/SS	155 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1852
Static Loaded Radius (mm)	866
Rolling Circumference (mm)	5648
SRI (mm)	900
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-00797
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	1785	2290	2790	3065	3295	3605	3875	-
40	1785	2290	2790	3065	3295	3605	3875	-
30	1910	2450	2990	3280	3530	3860	4150	-
10	2095	2735	3315	3955	4540	4715	5235	5815

Printed on 10/12/2023 11:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..